- d) root user
- Answer is d
- initrd is a file of Linux;
- a) Containing root file-system necessary during startup
- b) Contains only scripts for running during startup
- c) both a b
- d)None of these

View Answer d

- 3. when the system is booted, then which of the following is loaded in memory?
- a) shell
- b) scripts
- c) kernel
- d) commands

View Answer c

- The reason for starting up a computer called
- a) Bootstrapping
- b) Booting
- c) Boot loading
- d) Boot record

View Answer a

- 5.the another name of Bootstrapping
- a) cold boot
- b) quick boot
- c) Hot boot
- d) slow boot

View Answer a

- for Single <u>user mode</u> shell used is:
- a) bsh
- b) sh
- c) csh
- d) ksh

View Answer b

- 7. not a suitable run-level
- a) S
- b) 8
- c) 1
- d) 0

Answer b

- 8. Which one is partition mounted in Single user mode
- a) boot
- b) tmp
- c) root
- d) usr View Answer c

Courses

Core Multiple Choice Questions of Software Engineering

Multiple Choice Questions (MCQs) of data and databases

MCQs Elective Courses Computer Science

Computer Science MCQs Homepage

Microsoft MS Word MCQs

Introduction to Computing MCQs

Operating Systems

Networks MCQs

Digital Logic Design MCQs

Artificial Intelligence MCQs

Compiler Construction MCQs Computer Architecture MCQs

Discrete Mathematics MCQs

BASIC ELECTRONICS MCQs

Computer Graphics MCQs

HTML MCQs

Technical Report Writing MCQs

Digital Image processing MCQs

Mobile Android Applications MCQs

Advance Software Engineering MCQs

Software Testing MCQs

Web Security and Forensics MCQs

Viruses and Security

Microsoft Windows MCQs

HTML MCQs

Diode and Application Electronics MCQs

MCQs Analysis of Algorithms

CSS MCQs

PHP MCQs

Video Mixing MCQs

Computer Science MCQs Leaks PDF EBook by Fazal Rehman

Shamil

Java MCQs

Inheritance MCQs

MIS MCQs

Graphic Design MCQs

Series and Parallel Sequences

- 9. Which daemon manages the <u>physical memory</u> when another physical memory is required.
- a) process daemon
- b) init daemon
- c) swap daemon
- d) sched daemon

View Answer c

- 10. which function is started at the end of kernel bootstrap?
- a) /etc/kernel
- b) /etc/init
- c) /etc/user
- d) /etc/swap

Answer b

- 11. init process id is:
- a) -1
- b) 4
- c) 2
- d) 1

Answer is a

- 12. To get the default run level, which function is read by init
- a) /etc/kernel
- b) /etc/boot
- c) /etc/init
- d) /etc/inittab

View Answer d



Prof. Fazal Rehman Shamil

CEO @ **T4T**utorials.com

I welcome to all of you if you want to discuss about any topic. Researchers, teachers and students are allowed to use the content for non commercial offline purpose. Further, You must use the reference of the website, if you want to use the partial content for research purpose.

MCGS

Arrays MCQs Questions Answers – C++

Pointers Solved MCQs Questions Answers

Stacks Solved MCQs Questions Answers

WordPress MCQs Questions Answers

Corel DRAW Quiz Test Solved Mcqs Questions with Answers

Corel Draw MCQs for Graphic Designer Job Test

Operator overloading Solved MCQ's (OOP)

Polymorphism Mcqs In Object Oriented Programming(OOP)

Autocad Solved MCQs – Jobs Test

Social Networks MCQs Solved Questions Answers

Domain name system solved MCQs Quesitons Answers

ABRIVIATIONS stand for MCQs

Iterative Model MCQs Solved Questions Answers

C++ Array Solved MCQs Questions Answers

incremental Model Solved MCQs and Questions Answers

UML diagrams solved MCQs Questions Answers

Cyber Crime Solved MCQs Questions Answers.

Technology Management MCQs

Integrity constraints MCQ Answers

Database functions and procedure MCQs Answers

C++ STANDARD LIBRARY MCQs Questions Answers

Storage area network MCQs Questions Answers

PHP MyAdmin MCQs Questions Answers

Oracle MCQ's Questions Answers

WIFI MCQs